

Apéndice F. Modulaci3n realizada en obra.

| PANTALLAS | | | | | | | | | | | | | | | | | | | |
|-----------|----------|----------|-------|----------|-----|----|---------|------|-------------|-----|-----|----|-------|-----|----|----|----|-----|------------------|
| COLUMNA | CHAPETAS | TENSORES | PINES | CORBATAS | | | ANGULOS | | ALINEADORES | | | | LATAS | | | | | | RETRANQUES MM |
| | | | | 86 | 31 | 76 | 60 | 1.20 | 1 | 2 | 2.5 | 3 | 20 | 25 | 30 | 40 | 50 | 60 | |
| ADELANTE | A1 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| | B1 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| | C1 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| | E1 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| | D1 | 200 | 62 | 36 | | | 12 | 2 | 4 | 8 | | 8 | | 4 | 4 | 4 | | 8 | 12 |
| | A2 | 140 | 56 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| | A*2 | 140 | 15 | 10 | | 5 | | 2 | 4 | | 8 | | | 4 | | | | 8 | 6 |
| | B2 | 140 | 56 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| | C2 | 350 | 90 | 48 | 24 | | | 2 | 4 | 8 | | | 8 | 4 | | | | 20 | 14 |
| | D2 | 140 | 56 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| | E*2 | 140 | 15 | 10 | | 5 | | 2 | 4 | | 8 | | | | 4 | | | 8 | 6 |
| | E2 | 140 | 56 | 36 | 12 | | | 2 | 4 | 8 | | 8 | 8 | | | | | 16 | 12 |
| SUBTOTAL | | 2310 | 654 | 356 | 168 | 10 | 12 | 96 | 48 | 20 | 16 | 72 | 8 | 62 | 12 | 4 | 4 | 112 | 134 |
| ATRÁS | A4 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| | A*4 | 40 | 15 | 10 | | 5 | | 2 | 4 | | 8 | | | 4 | | | | 8 | 6 |
| | C3 | 80 | | | | | | 2 | 4 | | | | | | | | 8 | | 8 |
| | D3 | 80 | | | | | | 2 | 4 | | | | | | | | 8 | | 8 |
| | D4 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| | E*4 | 40 | 15 | 10 | | 5 | | 2 | 4 | | 8 | | | | 4 | | | 8 | 6 |
| | E4 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| | A5 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| | B5 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| | C5 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| | D5 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| | E5 | 200 | 62 | 36 | 12 | | | 2 | 4 | 8 | 8 | | 8 | | | | | 16 | 12 |
| SUBTOTAL | | 1400 | 526 | 302 | 144 | 10 | | 96 | 48 | 64 | 20 | | | 64 | 8 | | | 16 | 144 |
| TOTAL | | 4210 | 1180 | 664 | 312 | 20 | 12 | 192 | 96 | 144 | 96 | 72 | 8 | 132 | 20 | 4 | 4 | 16 | 258 |

Nota. Determinar los materiales necesarios por piso para las columnas del proyecto Palace Condominio teniendo en cuenta las dimensiones establecidas en el dise1o.